



PAB04 Smart Energy Flow Meter

- Wireless Valve on/off control
- Multi Kinds Flow meter compatible
- Z-Wave 500 Module Adopted
- Easy install and use
- With Easy Repeater Function
- Z-wave wireless systems integration
- With Z-wave S2 certification



Rated Voltage	6~24VDC
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (E U) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Measurement	
G1/8" YF-S401	2300 Pulse/Liter
G1/4" YF-S402	270 Pulse/Liter
G3/4" FS-300A	330 Pulse/Liter
G1" YF-G1*	60 Pulse/Liter*
Dimension	47.8(L) x 39.2(W) x 15.6(H) mm
Weight	32 g
IP classification	indoor use
Operation Temperature	-10~ 40°C
Operation Humidity	85%RH max

*The data is only for specific Water Sensor, http://wiki.seedstudio.com/G1_Water_Flow_Sensor/



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652