



## PAN05 Z-Wave Smart In Wall Switch

- Wireless switch on/off control
- Can control 1 Relay with 2 real buttons
- Interactive with other Devices
- With Easy Repeater Function
- Single And Stronger Relay Adopted



|                       |   |
|-----------------------|---|
| Rated Voltage         | 100~240V  |
| RF distance           | Min. 40M indoor,<br>100M outdoor line of sight,   |
| RF Frequency          | 908.4MHz,916MHz (U.S. A./Mexico)<br>868.4MH, 869.85MHz ( EU)<br>922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver |
| Chip                  | Z-wave 500 Series Module  |
| Output                |   |
| Current               | 11A   |
| Load                  | 2640W (Resistive Load, @240 V)  |
| Dimension             | 47.5(L) x 39(W) x 15.6(H) mm  |
| Weight                | 39.4g   |
| IP classification     | indoor use  |
| Operation Temperature | 0 ~ 40°C  |
| Operation Humidity    | 85%RH max   |



### PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan  
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652