



PAN09 Z-Wave Smart In Wall Switch

- Wireless switch on/off control
- Can control 2 Relay with 2 real buttons
- Interactive with other Devices
- 2 Relays and 2 Meters
- With Easy Repeater Function
- Single And Stronger Relay Adopted
- Match the power outlet panel in TW & JP



Rated Voltage	100~240V
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (E U) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Output	
Current	5A
Output Power	1100 W(Resistive Load, @230V/50Hz)
Measurement Error	3 W (Under 40 W) 5% (Above 40 W)
Dimension	43.85(L) x 22.76(W) x 40.35(H) mm
Weight	43.2g
IP classification	indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652