



CREATE SMART LIVING FOR YOU

www.philio-tech.com

In Wall Switch

PAN30



- Wireless switch on/off control
- Can control 2 Relay with 2 real buttons
- With Z-wave 700 S2 smart started
- Faster, Longer Distance, Lower Power consumption than Z-wave 500 chip
- Provide easy repeater function

S2



| | |
|-----------------------|---|
| Rated Voltage | 100-240V~ 50/60Hz |
| Maximum Load | 6.5A x 2 channels (Resistive Load, @230Vac / 120Vac) |
| RF Frequency | 908.4MHz,916MHz (U.S. A./Mexico) 868.4MHz, 869.85MHz (EU) 920.9MHz, 921.7MHz, 923.1MHz (TW/SG/Thai/KR) Transceiver |
| Chip | Z-wave 700 Series |
| RF distance | Min. 40M indoor, 100M outdoor line of sight, |
| Dimension | 47.5(L) x 39(W) x 15.6(H) mm |
| Weight | 40g |
| IP classification | indoor use; IP20 |
| Operation Temperature | 0 - 40°C |
| Operation Humidity | 85%RH max |



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652