



CREATE SMART LIVING FOR YOU

Z-Wave Smart Energy plug-in switch

PAN44

- Farther RF Transmit and Receive Range
- Monitoring Power Consumption Easily
- Turn Appliances On/Off Remotely
- With Easy Repeater Function
- Overload protection
- Interactive with other Devices



S2



Rated	100-240Vac 50-60Hz 13A
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 920.9MHz, 921.7MHz, 923.1MHz (TW/SG/Thai/KR) Transceiver
Chip	Z-wave 700 Series Module
Output	13A, Resistive only (@120Vac or @230Vac)
Overload Protection	14.5A
Measurement Error	3 W (Under 40 W) 5% (Above 40 W)
Dimension	65(L) x 44(W) x56(H) mm
Weight	65.8g
Location	Indoor use
Operation Temperature	0 to 40°C
Operation Humidity	85%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel: +886-2-2908-8952 Fax: +886-2-29088652