



PAT02-A 3 in 1 Flood Sensor

- With Flood, Humidity and Temperature All In One Small device
- Extremely low power consumption
- Build-In Buzzer
- Easy and quick to install
- Z-wave wireless systems integration



Rated Voltage	3.0 V by CR123
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Battery	CR123 1700mah
Battery Life	CR123 5 years
Measurement	
Temperature Accuracy	-10 ~ 40°C ±0.4°C
Humidity Accuracy	0 ~ 80% ±4 RH
Dimension	86(L) x 28(W) x 23(H) mm
Weight	55.6g
IP classification	IP20; indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652