

## PSA03 Electrical Door Lock

- Access methods: password & key
- Deadbolt detection
- Leading code function
- Z-Wave control with Security S2 protocol
- Add/Delete user's code individually
- Temporarily disable user code
- One-time-user code available
- Low battery alarm
- IP54 Zinc alloy and steel housing design



Features  
S2 Security



Rated Voltage	4.6~6.0V (Alkaline LR6 AA batteryx4)
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz ( EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Life Time	6 Months(Condition : Touch pad 10 times Remote 10 times to open/close door for one day)
Body Dimension	133(L) x 67(W) x 23.2(H)mm 189(L) x 73(W) x 27.1(H)mm
Lock Body Hole / Lock Latch Hole	Ø54mm / Ø25mm
Proper Door Thickness	35 ~ 45mm
Proper Backset	60 or 75 mm
Cylinder	5 pins Kwikset keyway standard, 6 pins Schlage keyway optional
IP classification	IP20; indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



### PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan  
sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652