



## PSC03 Z-wave Smart Gateway

- Compatible thousands of Z-wave Device
- Wireless 500 series Z-Wave module inside
- 1 external USB port (option 4G and Zigbee)
- Rechargeable Battery inside (optional)
- Multi SDK Command for customized
- Invisible Antenna design with good RF range
- Side LED for include/exclude/WPS indication
- SD card for storage
- Linux-based,
- Lowest power consumption



Rated Voltage	USB 5V 1A
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz ( E U) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
RF wireless	WiFi IEEE 802.11 b/g/n (>17dBm)
Software	Linux 2.6.36, Open WRT3.10
Dimension	110(L) x 110 (W) x 16 (H) mm
Weight	289g
IP classification	indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



### PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan  
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652