

PSM08 Z-Wave Door Sensor

- Farther RF Transmit And Receive Range
- Fits Your Home Decoration Style
- Easy to install
- Low Power Consumption
- Interactive with other Devices



Rated Voltage	3.0V by CR123
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Battery Lifetime	3 Year (Normal Operation Mode)
Sensitivity	Magnetic Gap 23 mm (open--> close) 27 mm (close--> open)
Dimension	Detector Dimension 85.87(L) x 24.97 (W) x 22(H)mm Magnet Dimension 45.91(L) x 12.08(W) x 11.5(H)mm
Weight	50g
IP classification	indoor use
Operation Temperature	-10 ~ 40°C
Operation Humidity	95%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652