



PSM09 Z-wave DoorLock Sensor

- Farther RF Transmit And Receive Range
- Detecting and feedback if the door is open/close and lock/unlock
- Two different kinds of types for user to choose
 - A Type – Door/Window/Lock status
 - B Type – Door/Window status
- Easy to install
- Low Power Consumption
- Interactive with other Devices



Rated Voltage	3.6V (ER14250 Battery)
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Battery Lifetime	Type A: 2 years typ. Type B: 3 years typ.
Sensitivity	Magnetic Gap 25 mm (open--> close) 30 mm (close--> open)
Dimension	55(L) x 27(W) x 33.2(H) mm
Weight	10.6g (Body) / 9.2g (Battery)
IP classification	indoor use
Operation Temperature	-10 ~ 40°C
Operation Humidity	95%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652