



PSP05 Z-Wave Motion Sensor

- Interactive with Other Z-wave Device
- Adopt Z-Wave 500 Module
- Compact design and easy installation
- Extremely Low Power Consumption
- Long Battery Life



Rated Voltage	3.0 V by CR123
RF distance(Z-wave)	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Battery	CR123A
Sensitivity	Wall Mount:8M Ceiling Mount: Mounting Height 4M Radius Distance 6M
Body Dimension	∅45.5 X 49.3 mm
Body Weight	120g
Body Dimension	∅ 71.2 X 10.9 mm
Bracket Weight	30g
IP classification	indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652